

Care Guide For All Flags

The life expectancy of your flag is dependent on the the care you provide. Flag fabrics are susceptible to damage caused by dirt, sun exposure, moisture and other damaging elements. To extend the life of your flag follow these basic recommendations:

- Wash your outdoor flag in mild detergent and thoroughly rinse prior to storage or use. Do not fold flag when wet.
- Indoor and parade flags should be dry cleaned.
- Repair your flag as soon as damage is visible. Repaired flags are acceptable as long as the overall dimensions are not noticeably altered.
- When flag is hoisted on a flagpole, keep clear from trees, wires and any other damaging objects.
- In severe weather, take your flag down and store.
- Take down your flag at dusk each day and re-hoist the next morning.
- Keep your flagpole free of rust and oxidation which will stain and damage your flag fabric.

Installation Guide

PLEASE READ BEFORE USE

If you have any issues with your flag, please contact us immediately




Installation Guide

Step 1

Remove poles from bag and check against component list to the right.

(Please Note 2.8m 2 pole kit. 3.4m 3 pole kit, 4.5m and 5.6m 4 pole kit)



Step 2

Insert pole **B** into pole **A**, pole **C** into pole **B** and pole **D** into pole **C** (*Largest to smallest*)




Step 3

Thread flag onto pole and pull taut ensuring that the pole is fully inserted into the strengthened end of the sleeve take care not to damage the sleeve while threading the flag onto the pole. Do not over bend the pole this could result in damage. Take the bungee and thread through the eyelet on the base of the flag. Creating a loop, thread the metal clip through the loop and pull tight. Attach to the retaining clip on the base of the pole and adjust if necessary



Step 4 For Rotating Ground Spike

Hammer rotating ground spike into the ground.
Place pole onto revolving spigot



Step 4 For Simple Ground Stake

Hammer simple ground stake into the ground.
Place pole over the simple ground stake.
(Please note ground stake is a loose fit)



Step 4 For Water Bag And Cross Base

Open out legs on the cross base, fill water bag and place onto cross base.
Place pole onto revolving spigot



Please note: Maximum wind speed 18mph

Installation Guide

Step 4 For Drive On Foot

Screw adapter into fixed spigot base



Step 5

Attached fixed spigot to under Wheel base using counter sunk screw provided



Step 6

Place pole onto fixed spigot




Step 4 For Large Water Base

Remove top bracket from top.
Turn the water base over and remove fixing bracket.
Place top bracket to the bottom of the water base.
Turn the water base upright. Push the fixing bracket into the base till it touches the bottom.




Step 5

Twist the fixing bracket in till tight. Turn the water base upright.
Push the fixing bracket into the base, place your flag pole into the fixing bracket and twist in till tight and place pole on to the spike.




Step 4 For Small Water Base

Turn the water base over and remove fixing bracket.



Step 5

Turn the water base upright. Push the fixing bracket into the base, place your flag pole into the fixing bracket and twist in till tight and place pole on to the spike.



Please note: Maximum wind speed 18mph